

# Vehicle Access Ladder

## Instructions for use


### Product overview

Ladder

Left hand bracket

Right hand bracket

Ladder feet



Handrail

Cam lock

Webbing strap

### Stage 1

- When transporting ladders ensure they are suitably placed to prevent damage.
- Before using a ladder at work a risk assessment should be carried out respecting the legislation in the country of use.
- Visually check the ladder is not damaged.
- Do not use a damaged ladder.
- Inspect product before use to confirm condition and operation of parts.
- Remove any contamination from the ladder such as mud, paint, oil or snow.
- Ensure that the user is fit enough to use the ladder.



### Stage 2

- Place ladder firmly on floor at a set distance away from the vehicle.
- The ladder should be on an even, level and unmovable base.
- When positioning the ladder take into account risk of collision with the ladder e.g. pedestrians, vehicles, or doors.
- Ladders should not be positioned on slippery surfaces.
- Identify any electrical risks in the work area.



### Stage 3

- Push release lever on cam lock with one hand.
- Pull through webbing strap with other.



### Stage 4

- Place your foot on the bottom rung to hold the ladder in place.
- Place your left hand on the left sliding bracket.
- Place your right hand on the handrail.




### Stage 5

- Slide both the brackets up the ladder stile until they are above the bed height.



### Stage 6

- Lean the ladder forward and lower the brackets in order for them to lie flush with the corner of the bed, to ensure the ladder is set to the correct angle.



# Vehicle Access Ladder


## Stage 7a

- Reach out with the straps to the nearest securing point.



## Stage 7b

- Place the wire hook onto the outside of the cross-beams.



## Stage 7c

- Place the wire hook under the side rave.




## Stage 8

- Place one hand on the side bracket and push it into the side of the lorry.
- With your other hand pull firmly on the webbing strap.



## Stage 9

- Make sure the ladder is located centrally and the straps are of equal length.
- Do not climb onto ladder before it has been fully secured.
- The angle of the straps must be between a minimum of 10° and a maximum of 45°.



## Stage 10

- Keep a firm grip on the hand rail when ascending and descending.
- Face the ladder when ascending and descending.
- Do not exceed the maximum total load for the type of ladder.
- Wear suitable footwear when climbing the ladder.



## Stage 11

- Step off the ladder to the left hand side.
- Do not climb on any rungs above bed height.
- Do not use the top tread if the side rave of the lorry locates behind it.



For further information about this product or any other products and services, please contact :

**Youngman Group Ltd**  
The Causeway, Maldon,  
Essex, CM9 4LJ,  
United Kingdom

t +44 (0)1621 745900  
f +44 (0)1621 859845  
e sales@youngmangroup.com

youngmangroup.com